

Chimney Installation Shopping List

Torch TS-65F / TS-85F Through-Ceiling Installation

#	Item Description	Product Link
CLASS A CHIMNEY COMPONENTS		
1	Class A Chimney Pipe: 36"	Menards - SuperVent 6" ID x 36"
2	Finishing Band	Menards - Selkirk Universal Finishing Band
3	Chimney Adapter	Menards - SuperVent 6" Adapter
4	Chimney Cap	Menards - SuperVent 6" Deluxe Rain Cap
5	Ceiling Support	Menards - SuperVent 6" Ceiling Support
6	Storm Collar	Menards - SuperVent 6" Storm Collar
ROOF PENETRATION AND SEALING		
7	Silicone Roof Boot (7")	Fasteners Plus - Gray Silicone Flashing Boot
8	High Temp Silicone	Amazon - Sika High Temp Silicone
9	Roof Screws	Amazon - Roofing Screws
BLACK STOVE PIPE (Single or Double Wall)		
10	Telescoping Black Stove Pipe	Menards - Selkirk 6" Telescoping Pipe
11	Telescoping Small	Menards - Selkirk 6" Small Telescoping Pipe
12	Black Stove Pipe - 6"	Menards - Selkirk 6" x 6" Black Pipe
13	Black Stove Pipe - 12"	Menards - Selkirk 6" x 12" Black Pipe
14	Black Stove Pipe - 24"	Menards - Selkirk 6" x 24" Black Pipe

Note: This is the recommended chimney configuration for the Torch TS-65F and TS-85F gas sauna stoves in a through-ceiling installation. Both models take a 6 inch Class A all-fuel chimney rated for at least 800 F, and the flue must terminate vertically above the roof.

Always follow local building codes and the manufacturer installation instructions. Consult a professional installer if needed.